

The Flexxifinger Quicker Picker rotary rock picker attaches to any skid steer or tractor equipped with a universal quick-attach mount and a standard hydraulic flow. Any debris smaller than 2"/5cm will fall between the solid steel bars during the barrel's spinning motion, resulting in more dirt left in the field.

HEAVY-DUTY

VERSATILE

)

EFFICIENT

>







Flexifinger & Dicker Picker

ROTARY ROCK PICKER

echnical specifications



MODEL 800

Dimensions	163cm x 122cm x 104cm
Drum length	121.9cm
Drum diameter	91.4cm
Capacity	907kg
Drive	Direct (Gear)
Spin direction	Counterclockwise
Spindle size	11.4cm (9072kg)
Bars	25mm solid steel
Back plate	19mm solid steel
Rock size	5cm – 76cm
Loader ROC	1442kg
Skid steer size	More than 60 HP
Attaches with	Quick-attach plate
Weight	528kg
Hydraulic couplers	Flat-faced couplers (included)
Hydraulic flow	Standard flow (26.51)
Hydraulic hose	13mm NPT
Hydraulic limit	1100psi (f) / 500 psi (r) . 76 bar (f) / 34 bar (r)

The Flexxifinger® Quicker Picker is the first rotary-style rock picker designed for skid loader use. Using a universal quick-attach plate, the Flexxifinger® Quicker Picker can be mounted on virtually any skid steer or loader.

To clear an area of debris, the operator scoops up the debris and, using the loader's auxiliary hydraulic controls, spins the barrel. This spinning motion causes the debris to collide inside the barrel which knocks off excess soil and dirt. Any soil or debris smaller than 5cm in diameter will fall between the bars, leaving only debris larger than 5cm in the barrel. The Flexxifinger® Quicker Picker rotary rock picker is ideal for use in several industries including agricultural, industrial, maintenance, mining, landscaping and forestry.









YOUR FLEXXIFINGER® QUICKER PICKER DEALER

Flexifinger (25)
1-800-925-1510 (1-800-544-8512 (1-800-544-8512 (1-800-544-8512 (1-800-874-08881 (1-800-874-