

QUESTIONS TO ASK

Determine which model is best | Flexifinger® Quicker Picker

The Flexifinger® Quicker Picker Rotary Rock Picker is available in 2 different models. The function and method of attachment of both models are the same – the difference between the two is mainly in size and capacity.

In order for the customer or loader operator to safely use the Flexifinger® Quicker Picker to its full capacity, it is important to ensure that the loader is capable of handling the maximum possible weight of a full barrel of rocks/debris.

Before recommending any Flexifinger® Quicker Picker to a customer, there are a few questions to ask that will dictate the options available to the customer.

1. To determine the correct fit:

- a. What is the make and model of your skid-steer, loader or tractor?

The Flexifinger® Quicker Picker is compatible with a Universal Quick-Attach mounting plate which is standard on most skid-steers. If the customer will be using the Flexifinger® Quicker Picker with a loader or tractor, the loader or tractor may require a special adapter plate to accommodate the Universal Quick-Attach mounting plate.

2. To determine the possible model(s) to recommend:

- a. What is the maximum lifting capacity of the skid-steer, loader or tractor?

To safely use the Flexifinger® Quicker Picker, the skid-steer, loader or tractor must be rated to lift the combined weight of a barrel full of rocks/debris plus the rock picker unit itself. For safety reasons, Flexifinger cannot recommend a unit to a customer who does not meet this minimum lift capacities, since the customer cannot use the unit without the possibility of over-burdening the skid-steer, loader or tractor and/or increasing the potential risk for injury to the operator and damage to the equipment.

Due to the varying size, mass and density of rocks and debris, estimating the weight a partially filled barrel is not possible; therefore, recommending a model of the Flexifinger® Quicker Picker that can only be partially filled is inadvisable.

The minimum lift capacities for each model is:

- Model 400: 1660 lbs / 752 kg*;
- Model 800: 3220 lbs / 1461 kg.

** Model 400 is only available in select countries. Contact Flexifinger Sales & Support team for more details.*