

The Flexxifinger[®] Quicker Picker rotary rock picker attaches to any skid steer or tractor equipped with a universal quick-attach mount and a standard hydraulic flow. Any debris smaller than 2"/5cm will fall between the solid steel bars during the barrel's spinning motion, resulting in more dirt left in the field.

| HEAVY-DUTY | > |
|------------|---|
| VERSATILE | > |
| EFFICIENT | > |








Flexifinger ()) QUICKER PICKER ROTARY ROCK PICKER







| | Drum length | 36″ / 91.44 cm | 48″ / 121.92cm |
|--|----------------------|--|--|
| | Drum diameter | 30″ / 76.20 cm | 36″ / 91.44cm |
| | Capacity | 900 lbs / 408 kg | 2000lbs / 907kg |
| | Drive | Direct (Gear) | Direct (Gear) |
| | Spin direction | Counterclockwise | Counterclockwise |
| | Spindle size | 3" (7500 lbs) / 7.62cm (3402kg) | 4.5" (20000 lbs) / 11.43cm (9072kg) |
| | Rock size | 2″ – 28″/ 5cm-71cm | 2" – 34"/ 5cm – 76cm |
| | Loader lift required | 1660 lbs / 752kg | 3165 lbs / 1442kg |
| | Weight | 760 lbs / 344kg | 1165 lbs / 528kg |
| | Hydraulic flow | Standard flow (7 gal / 26.5l) | Standard flow (7 gal / 26.5l) |
| | Hydraulic hose | 0.5"/13mm NPT | 0.5" / 13mm NPT |
| | Hydraulic limit | 1100psi (f) / 500 psi (r) 76 bar (f) / 34 bar (r) | 1100psi (f) / 500 psi (r) 76 bar (f) / 34 bar (r) |
| | | | |



To clear an area of debris, the operator scoops up the debris and, using the loader's auxiliary hydraulic controls, spins the barrel. This spinning motion causes the debris to collide inside the barrel which knocks off excess soil and dirt. Any soil or debris smaller than 2"/5cm in diameter will fall between the bars, leaving only debris larger than 2"/5cm in the barrel. The Flexxifinger® Quicker Picker rotary rock picker is ideal for use in several industries including agricultural, industrial, maintenance, mining, landscaping and forestry.

YOUR FLEXXIFINGER® QUICKER PICKER DEALER







